

PICTURE SHOW	MODEL NO.		SPECIFICATION
	<p>AS-N0810D</p>		<p>Compression Method: H.264 High Profile IP Camera Input: 8CH (1920*1080, 1280*960, 1280*720, etc) Video Output: 1CH VGA Out, 1CH HDMI 1080P Out Recording Resolution: 8CH *1080P/8CH*960P/8CH*720P, etc (All Real Time) Preview Resolution: 8CH*D1/1CH*1080P Playback Resolution: 1CH*1080P Recording Mode: Timer/Motion Detection 1 SATA 2.5" Hard Disk Interface, Support Max 4TB Memory RJ-45 Ethernet Connector, Static IP, P2P, Backup: 2 x USB2.0 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup Color Optional: White or Black Power Input: DC5V, 2A (Adapter Included) Dimension: 114*110*40mm (L*W*H), Weight: 0.5Kgs</p>
	<p>AS-N0810A</p>		<p>Compression Method: H.264 High Profile IP Camera Input: 8CH (1920*1080, 1280*960, 1280*720, etc) Video Output: 1CH VGA Out, 1CH HDMI 1080P Out Recording Resolution: 8CH*1080P/8CH*960P/8CH*720P, etc (All Real Time) Preview Resolution:8CHxD1 /1CHx1080P Playback Resolution: 1CH*1080P Recording Mode: Timer/Motion Detection 1 SATA 2.5"/ 3.5" Hard Disk Interface, Support Max 4TB Memory RJ-45 Ethernet Connector, Static IP, P2P, Backup: 2 x USB2.0 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup Color Optional: White or Black Power Input: DC12V, 2A (Adapter Included) Dimension: 215*215*53mm (L*W*H), Weight: 2Kgs</p>
	<p>AS-N0860T</p>		<p>Compression Method: H.264 High Profile IP Camera Input: 8CH (1920*1080, 1280*960, 1280*720, etc) Video Output: 1CH VGA Out, 1CH HDMI 1080P Out Recording Resolution: 8CH* 1080P/8CH*960P/8CH*720P, etc (All Real Time) Preview Resolution: 8CH*D1/1CH*1080P Playback Resolution: 1CH*1080P Recording Mode: Timer/Motion Detection 2 SATA Hard Disk Interface, Support Max 8TB Memory RJ-45 Ethernet Connector, Static IP, P2P, Backup: 2 x USB2.0 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup Color Optional: White or Black Power Input: DC12V, 3A (Adapter Included) Dimension: 354*263*50(mm) Weight: 4.5kg</p>



AS-N0850

Compression Method: H.264 High Profile
 IP Camera Input: 8CH (1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Out, **1CH HDMI 1080P Out**
 Recording Resolution: 8CH***1080P**/8CH*960P/8CH*720P, etc **(All Real Time)**
 Preview Resolution: 8CH*D1/1CH*1080P
 Playback Resolution: 1CH*1080P
 Recording Mode: Timer/Motion Detection
2 SATA Hard Disk Interface, Support Max 8TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Color Optional: White or Black
 Power Input: DC12V, 3A (Adapter Included)
 Dimension: 354*263*50(mm) Weight: 4.5kg

25CH 1080P NVR

Wiztec Security Your World Secure

PICTURE SHOW

MODEL NO.

SPECIFICATION



AS-N2560T

Compression Method: H.264 High Profile
 IP Camera Input: 25CH (**2592*1944, 2048*1536**, 1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Out, **1CH HDMI 1080P Out**
 Recording Resolution: **25CH *1080P**/25CH*960P/25CH*720P, etc**(All Real Time)**
 Preview Resolution: 25CH*D1/16*D1/9CH*D1/4CH*D1/1CH*1080P
 Playback Resolution: **4CH*1080P**
 Recording Mode: Timer/Motion Detection
2 SATA Hard Disk Interface, Support Max 8TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Power Input: DC12V, 3A (Adapter Included)
 Dimension: 354*263*50(mm) Weight: 4.5kg



AS-N2550H

Compression Method: H.264 High Profile
 IP Camera Input: 25CH (**2592*1944, 2048*1536**, 1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Out, **1CH HDMI 1080P Out**
 Recording Resolution: **25CH *1080P**/25CH*960P/25CH*720P, etc**(All Real Time)**
 Preview Resolution: 25CH*D1/16*D1/9CH*D1/4CH*D1/1CH*1080P
 Playback Resolution: **4CH*1080P**
 Recording Mode: Timer/Motion Detection
2 SATA Hard Disk Interface, Support Max 8TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Power Input: DC12V, 3A (Adapter Included)
 Dimension: 354*263*50(mm) Weight: 4.5kg



AS-N2530

Compression Method: H.264 High Profile
 IP Camera Input: 25CH (2592*1944, 2048*1536, 1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Out, 1CH HDMI 1080P Out
 Recording Resolution: **25CH *1080P**/25CH*960P/25CH*720P, etc(**All Real Time**)
 Preview Resolution: 25CH*D1/16*D1/9CH*D1/4CH*D1/1CH*1080P
 Playback Resolution: **4CH*1080P**
 Recording Mode: Timer/Motion Detection
2 SATA Hard Disk Interface, Support Max 8TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Power Input: DC12V, 5A (Adapter Included)
 Dimension: 405*325*65mm (L*W*H), Weight: 6Kgs



AS-N2580

Compression Method: H.264 High Profile
 IP Camera Input: 25CH (2592*1944, 2048*1536, 1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Out, 1CH HDMI 1080P Out
 Recording Resolution: **25CH *1080P**/25CH*960P/25CH*720P, etc(**All Real Time**)
 Preview Resolution: 25CH*D1/16*D1/9CH*D1/4CH*D1/1CH*1080P
 Playback Resolution: **4CH*1080P**
 Recording Mode: Timer/Motion Detection
2 SATA Hard Disk Interface, Support Max 8TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Power Input: DC12V, 5A (Adapter Included)
 Dimension: 405*325*65mm (L*W*H), Weight: 6Kgs

25CH 1080P 8HDD NVR

Wiztec Security Your World Secure

PICTURE SHOW

MODEL NO.

SPECIFICATION



AS-N2590K

Compression Method: H.264 High Profile
 IP Camera Input: 25CH (2592*1944, 2048*1536, 1920*1080, 1280*960, 1280*720, etc)
 Video Output: 1CH VGA Output, 1CH HDMI Output
 Recording Resolution: **25CH *1080P**/25CH*960P/25CH*720P, etc(**All Real Time**)
 Preview Resolution: 25CH*D1/16*D1/9CH*D1/4CH*D1/1CH*1080P
 Playback Resolution: **4CH*1080P**
 Recording Mode: Timer/Motion Detection
8 SATA Hard Disk Interface, Support Max 32TB Memory
 RJ-45 Ethernet Connector, Static IP, **P2P**, Backup: 2 x USB2.0
 Remote Viewable by Smart Phone/Computer/Tablet With Internet Access
 Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
 Power Input: AC120V~240V
 Dimension: 442*437*92(mm) (L*W*H), Weight: 9Kgs


4CH 1080P POE NVR

Wiztec Security Your World Secure

PICTURE SHOW	MODEL NO.		SPECIFICATION
	<p>AS-N0410HAP</p>		<p>Compression Method: H.264 High Profile</p> <p>IP Camera Input: Max 4CHx1080P (Total Incoming Bandwidth ≤20M)</p> <p>Video Output: 1CH VGA Out, 1CH HDMI 1080P Out</p> <p>Recording Resolution: 2MP/1.3MP/1MP</p> <p>Frame Rate: Main Stream: 25fps (PAL) / 30fps (NTSC) Sub-stream: 25fps (PAL) / 30fps (NTSC)</p> <p>POE: 4 x Independent 100Mbps PoE Network Interfaces (Output Power ≤15.4W per Interface)</p> <p>Preview Resolution: 1CH@Main Stream/4CH@Sub-stream</p> <p>Playback Resolution: Support Single Channel/Four Channels Mode</p> <p>1 SATA 2.5"/ 3.5" Hard Disk Interface, Support Max 4TB Memory</p> <p>5xRJ-45(10M/100M Adaptive Ethernet Interface), Backup: 2 x USB2.0</p> <p>Static, Dynamic IP and DDNS, P2P, Support IE and Special Client Software</p> <p>Remote Viewable by Smart Phone/Computer/Tablet With Internet Access</p> <p>Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup</p> <p>Backup: USB2.0 (such as U Disk, USB Drive) and Network</p> <p>Power Input: DC 48V ≤10W (Without Hard Disk and POE)</p> <p>Dimensions (L×W×H): 215*215*53(mm) Weight: 2kg</p>

8CH 1080P POE NVR

ACESEE Secure Your World

PICTURE SHOW	MODEL NO.		SPECIFICATION
	<p>AS-N0860TP</p>		<p>Compression Method: H.264 High Profile</p> <p>IP Camera Input: Max 9CHx1080P (Total Incoming Bandwidth ≤46M)</p> <p>Video Output: 1CH VGA Out, 1CH HDMI 1080P Out</p> <p>Recording Resolution: 2MP/1.3MP/1MP</p> <p>Frame Rate: Main Stream: 25fps (PAL) / 30fps (NTSC) Sub-stream: 25fps (PAL) / 30fps (NTSC)</p> <p>POE: 8 x Independent 100Mbps PoE Network Interfaces (Output Power ≤15.4W per Interface)</p> <p>Preview Resolution: 1CH@Main Stream/9CH@Sub-stream</p> <p>Playback Resolution: Support Single Channel/Four Channels Mode.</p> <p>2 SATA 2.5"/ 3.5" Hard Disk Interface, Support Max 8TB Memory</p> <p>9xRJ-45(10M/100M Adaptive Ethernet Interface), Backup: 2 x USB2.0</p> <p>Static, Dynamic IP and DDNS, P2P, Support IE and Special Client Software</p> <p>Remote Viewable by Smart Phone/Computer/Tablet With Internet Access</p> <p>Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup</p> <p>Backup: USB2.0 (such as U Disk, USB Drive) and Network</p> <p>Power Input: DC 48V ≤10W (Without Hard Disk and POE)</p> <p>Dimensions (L×W×H): 354*263*50(mm) Weight: 4.5kg</p>



AS-N0850P

Compression Method: H.264 High Profile

IP Camera Input: Max 9CHx1080P (Total Incoming Bandwidth ≤46M)

Video Output: 1CH VGA Out, **1CH HDMI 1080P Out**

Recording Resolution: 2MP/1.3MP/1MP

Frame Rate: Main Stream: 25fps (PAL) / 30fps (NTSC)

Sub-stream: 25fps (PAL) / 30fps (NTSC)

POE: 8 x Independent 100Mbps PoE Network Interfaces
(Output Power ≤15.4W per Interface)

Preview Resolution: **1CH@Main Stream/9CH@Sub-stream**

Playback Resolution: Support Single Channel/Four Channels Mode.

2 SATA 2.5"/ 3.5" Hard Disk Interface, Support **Max 8TB** Memory

9xRJ-45(10M/100M Adaptive Ethernet Interface), Backup: 2 x USB2.0

Static, Dynamic IP and DDNS, **P2P**, Support IE and Special Client Software

Remote Viewable by Smart Phone/Computer/Tablet With Internet Access

Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup

Backup: USB2.0 (such as U Disk, USB Drive) and Network

Power Input: DC 48V ≤10W (Without Hard Disk and POE)

Dimensions (L×W×H): 354*263*50(mm) Weight: 4.5kg